Pulltarps® SuperShield™ Systems

SuperShield™ 9500E & 9500M Systems





SuperShield™ 9500E System

The reliable 1.3 HP Pulltarps® Electric Motor can be operated by an in-cab switch or an external switch. The system can hold up to 40 feet of tarp.



SuperShield™ 9500M System

The external ratcheting spring adjustment allows for easy spring tensioning in the field and can hold up to 30 feet of tarp.



Pulltarps® SuperShield™ System



SuperShield™ 9500E System Advantages

Automatic System

This is the strongest, most durable Automatic System available in the industry and is designed for longer applications up to 40 feet.

The fully welded 12 gauge steel construction offers the best protection from falling debris.

Telescoping arms sections for easy installation and adjustment.

The system can be ordered with the 12V Deluxe High Amperage Switch Kit and can be operated from inside the cab.

Powerful 1.3 HP Pulltarps® Electric Motor is backed by a 5 year prorated warranty.

SuperShield™ 9500M System Advantages

Semi-Automatic System

Designed for longer applications up to 30 feet, this system is fully powder coated and is radiused for superior strength.

The external ratcheting system allows for easy spring tensioning in the field.

Works great for hauling dirt, sand, aggregate and asphalt and is the most economical system for dump trucks.

This system can be upgraded to manual or fully automatic arm systems and are fast and simple to use.

SuperShield™ 9500E (Automatic) System

Designed for longer applications up to 40'.

- Powder coated finish and radiused for strength
- Telescoping arms for easy installation and adjustment
- 12V Deluxe High Amperage Switch Kit
- 1.3 HP Pulltarps® Electric Motor



SuperShield™ 9500M (Semi-Automatic) System

Designed for longer applications up to 30'.

- Powder coated finish and radiused for strength
- External ratcheting system allows for easy spring tensioning
- Is the most economical system for a dump truck
- Can be upgraded to a fully automatic system



Enclosed 4-Spring Pivot (Automatic)


Designed for applications up to 22'.

- Powder coated
- UHMW bearings for smooth operation
- Compact and fully enclosed four spring housing
- Can be mounted in the high or low positions

Single Spring Pivot (Automatic)

Designed for applications up to 40'.

- Pivots on UHMW bushings
- Fully enclosed single spring housing
- Handles applications up to 40'
- Available with steel or aluminum arms





Pulltarps® Tarps are Simply The Best!



HD Mesh

- 11oz. Heavy-Duty Mesh
- Grommets Every 3 Feet
- Seamless, Full-Width Tarps
- Reinforced with Webbing Along the Length of Each Side




Super HD Mesh

- 18oz. Super Heavy-Duty Mesh
- Grommets Every 3 Feet
- Seamless, Full-Width Tarps
- Reinforced with Webbing Along the Length of Each Side



Vinyl

- 18oz. Vinyl is Waterproof
- Grommets Every 3 Feet
- Seamless, Full-Width Tarps
- Reinforced with Webbing Along the Length of Each Side



Asphalt

- 16oz. Rated for 400-degrees
- Grommets Every 3 feet
- Urethane Coating
- Waterproof Fabric
- Seamless, Full-Width Tarps



A Safe Fleet Brand Pulltarps.com



Pulltarps.com



Copyright ©2021 Safe Fleet and its subsidiaries. All rights reserved. No part of this publication may be reproduced by any means without written permission from Safe Fleet. The information in this publication is believed to be accurate. However, Safe Fleet does not make any representation or warranty to that effect and does not assume responsibility for any consequences resulting from use of such information. Revisions or new editions of the publication may be issued (or not issued) in our discretion to incorporate such changes.



